MOVE FORWARD WITH *FAST-THINKING*, ADAPTABLE TECHNOLOGY

Canon imageRUNNER ADVANCE

4500i Series



- Compact A3 Monochrome device
- Prints up to 51 ppm in Black & White
- Scans up to 160 ipm
- Supports wide range of paper types and sizes
- Includes compact inner finisher

The imageRUNNER ADVANCE 4500i series presents advanced usability and a range of speed options to suit the needs of every workplace. As part of the GEN III platform, these compact machines are designed to save money while acting as a pivotal point for workflow management.

PERFORMANCE

Save time and resources thanks to advanced usability functions

- A3 mid- to low-volume Monochrome device with four speeds
- Standard single pass duplex scanning ADF enables high-speed scanning of 160 ipm (300 dpi, duplex)
- Large 10.1 inch full colour WVGA LCD touchscreen interface designed for a user-friendly experience
- High-capacity paper-handling abilities for a wide range of sizes and paper types
- Space-saving Inner Finisher incorporates ECO-Staple, Staple, and Staple-On-Demand functionalities
- My ADVANCE functions allow users to create their own personalised experience, tailored to meet their unique needs

COST CONTROL

Improve cost management in the workplace with strategic operation efficiencies

- Forced Job Hold and automatic blank page removal helps to reduce unnecessary paper wastage
- Ability to change print settings at device for controlled output

INTEGRATION

Seamlessly integrate with key line-of-business systems

- Common Source Code for Firmware
- Collaborate with key line of business applications and external systems
- Personalised workflows give users the ability to take control of the way they want to manage their information so that it works best for them
- Leverage Canon's MEAP platform to optimise processes with a range of powerful document, capture and output management solutions

SUSTAINABILITY

Incorporating responsible design and efficient operation to help achieve environmental goals

- Motion sensor/sleep recovery triggers contribute to reducing energy emissions
- Low energy consumption works consistently while machines are operating
- Machines are made with 100% recycled plastics and bio-based plastics are used on some parts of the main unit's exterior
- EPEAT-rated and ENERGY STAR qualified

Canon

SECURITY

Safeguard data and ensure sensitive information remains secure

- Standard HDD Encryption works to prevent data leaks and keep confidential information protected
- Security settings have been consolidated to reduce administration
- Security policy support is also available

MOBILITY

Advanced Mobile OS Support empowers workers through freedom and flexibility

- Mobile workflows are set up to easily allow users to connect, print, scan and capture using Canon PRINT Business
- Full support for Apple and Android Mobile Printing
- Simple and easy mobile connectivity with in-built WiFi

CONFIGURATION



Booklet Finisher

- 2-tray, 3,250 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-Demand 50 sheets (80 gsm)
- Supports optional internal 2/3, 2/4 and 4 hole inner punchers



Staple Finisher

- 2-tray, 3,250 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-Demand 50 sheets (80 gsm)
- Supports optional internal 2/3, 2/4 and 4 hole inner punchers



Inner 2Way Tray

- Separates copies, prints and faxes
- Adds a second internal output tray



Buffer Pass Unit

- Transports paper to external finisher



Inner Finisher

- 2-tray, 545 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-Demand 40 sheets (80 gsm)
- Supports optional internal 2/3, 2/4 and 4 hole inner punchers





Utility Tray



Paper Deck Unit

- Supports up to A4
- Media weight 60-128 gsm
- 2,700 sheets (80 gsm)



Cassette Feeding Unit

- Supports up to A3
- Media weight 60-128 gsm
- 2 x 550 sheets (80 gsm)



High Capacity Cassette Feeding Unit

- Supports up to A4
- Media weight 60-128 gsm
- 2,450 sheets (80 gsm)

imageRUNNER ADVANCE 4500i Series

Main Unit

Type	Monochrome Laser Multifunctional
Core Function	Print, Copy, Scan, Send, Store and Optional Fax
Processor	Canon Dual Custom Processor (Shared)
Control Panel	10.1 inch TFT LCD WSVGA Colour Touchpanel
Memory	Standard: 3.0GB RAM
Hard Disk Drive	Standard: 250GB Maximum: 1TB
Mirroring Hard Disk Drive	Optional: 250GB, 1TB
Interface Connection	Network: Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n), Optional: NFC, Bluetooth Others: Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device) Optional: Serial Interface, Copy Control Interface
Paper Capacity (A4, 80gsm)	Standard: 1,180 Sheets Maximum: 6,330 Sheets
Paper Sources (A4, 80gsm)	Standard: Two 550-sheet Paper Cassettes, 80-sheet Multi-purpose Tray Optional: Dual 550-sheet Paper Cassettes (Cassette Feeding Unit-AN1) 2,450-sheet Paper deck (High Capacity Cassette Feeding Unit-B1), 2,700-sheet Paper deck (Paper Deck Unit-F1) Maximum: 6,330 Sheets
Paper Output Capacity (A4, 80gsm)	Standard: 250 Sheets Maximum: 3,350 Sheets (with External Finisher)
Finishing Capabilities	Standard: Collate, Group With Inner Finisher : Collate, Group, Offset, Staple, *Hole Punch, Staple-Free Staple, Staple On Demand * Necessary for Inner 2/3 Hole Puncher-C1 or Inner 2/F4 Hole Puncher-C1 With External Finisher : Collate, Group, Offset, Staple, **Booklet, *Hole Punch, Staple-Free Staple, Staple On Demand * Necessary for 2/3 Hole Puncher Unit-A1 or 2/4 Hole Puncher Unit-A1 or 4 Hole Puncher Unit-A1 **Booklet Finisher-Y1 Only
Supported Media Types	Cassettes 1/2: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper Cassettes 3/4 (Cassette Feeding Unit-AN1): Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper Cassette Deck (High Capacity Cassette Feeding Unit-B1): Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper Multi-purpose tray: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency, Tracing paper, Label, Bond paper, Envelope Paper Deck Unit-F1: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper
Supported Media Sizes	Cassette 1: Standard Size: B4, A4, A4R, B5, B5R, A5R Custom Size : 139.7 mm x 182 mm up to 297 mm x 390 mm Cassette 2: Standard Size: A3, B4, A4, A4R, B5, B5R, A5R Custom Size: 139.7 mm x 182 mm up to 297 mm x 431.8 mm Cassette 3/4 (Cassette Feeding Unit-AN1): Standard Size: A3, B4, A4, A4R, B5, B5R, A5R Custom Size: 139.7 mm x 182 mm up to 297 mm x 431.8 mm Cassette Deck (High Capacity Cassette Feeding Unit-B1): A4 Multi-purpose tray: Standard Size: A3, B4, A4, A4R, B5, B5R, A5, A5R, Envelopes: (No. 10 (COM 10), Monarch, ISO-C5, DL) Custom Size : 98 mm x 148 mm up to 297 mm x 431.8 mm Paper Deck Unit-F1: A4, B5
Supported Media Weights	Cassettes 1/2: 60 to 128 gsm Multi-purpose tray: 52 to 220 gsm Duplex: 60 to 105 gsm
Warm-up Time	From Power On: 24 Seconds or Less. (Time between device power-on and when the start key is enabled (not print reservation) Quick startup Mode ON) From Deep Sleep Mode: 10 Seconds or Less Quick Startup Mode: 4 Seconds or Less
Dimensions (W x D x H)	587 mm x 740 mm x 945 mm
Installation Space (W x D)	Basic: 889 mm x 1,171.9 mm (when attach with Single Pass DADF-A1 + Multi-purpose tray open + Cassette Drawers open) Fully Configured: 1,811 mm x 1,269.9 mm (when attach with Single Pass DADF-A1 + Paper Deck Unit-F1 + Booklet Finisher-Y1 + Cassette Drawers open)
Weight*	Approx. 86.6kg (when attach with Single Pass DADF-A1) Approx. 81.3kg (when attach with DADF-AV1) *Including the toner bottle

Print Specifications

Printing Method	Monochrome laser beam printing
Print Speed	iR-ADV 4551i: 51 ppm (A4), 37 ppm (A4R), 25 ppm (A3), 18 ppm (A5R) iR-ADV 4545i: 45 ppm (A4), 32 ppm (A4R), 22 ppm (A3), 18 ppm (A5R) iR-ADV 4535i: 35 ppm (A4), 32 ppm (A4R), 22 ppm (A3), 18 ppm (A5R) iR-ADV 4525i: 25 ppm (A4), 17 ppm (A4R), 15 ppm (A3), 14 ppm (A5R)
Print Resolution*	1,200 dpi x 1,200 dpi *Laser Resolution
Page Description Languages	UFR II, PCL6, Adobe PS 3 (Option)
Double Sided Printing	Automatic (Standard)
Direct Print	Direct printing available from USB memory key, Advanced box, Remote UI and Web Access (Only PDF print from websites is supported) Supported File Types: PDF, TIFF, JPEG, EPS, XPS
Printing from Mobile and Cloud	A range of software and MEAP-based solutions is available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.
Fonts	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T* (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts** *Requires optional PCL International Font Set-A1 **Require optional Barcode PRT KIT-D1 PS fonts: 136 Roman
Print Features	Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Toner Reduction, Poster Printing
Operating System	UFRII: Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10, MAC OS X (10.6.8 or later) PCL: Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10 PS: Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10, MAC OS X (10.6.8 or later) PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows Vista/Windows 7/Windows 8/Windows8.1/Windows10

Copy Specifications

Copy Speed	iR-ADV 4551i: 51 ppm (A4), 37 ppm (A4R), 25 ppm (A3), 18 ppm (A5R) iR-ADV 4545i: 45 ppm (A4), 32 ppm (A4R), 22 ppm (A3), 18 ppm (A5R) iR-ADV 4535i: 35 ppm (A4), 32 ppm (A4R), 22 ppm (A3), 18 ppm (A5R) iR-ADV 4525i: 25 ppm (A4), 17 ppm (A4R), 15 ppm (A3), 14 ppm (A5R)
*First-Copy-Out Time (A4)	iR-ADV 4551i: Approx. 3.7 seconds or less (*20 °C to 30 °C Environment) iR-ADV 4545i/4535i: Approx. 3.8 seconds or less (*20 °C to 30 °C Environment) iR-ADV 4525i: Approx. 5.2 seconds or less (*20 °C to 30 °C Environment)
Copy Resolution	Reading: 600 dpi x 600 dpi Printing: Up to 1,200 dpi x 1,200 dpi (Printing Resolution)
Multiple Copies	Up to 999 copies
Copy Exposure	Automatic or Manual (10 Levels)
Magnification	25% - 400% (1% Increments)
Preset Reductions	25%, 50%, 70%, 81%, 86%
Preset Enlargements	115%, 122%, 141%, 200%, 400%
Basic Copy Features	Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favourite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel
Special Copy Features	Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Store in Mail Box, Superimpose Image, Cascade Copy, Copy ID Card, Detect Feeder Multi Sheet Feed, Free Size Original

Scan Specifications

Type	Single-pass Duplexing Automatic Document Feeder
Document Feeder Paper Capacity	150 Sheets (80gsm)
Document Feeder Supported Media Sizes	A3, B4, A4, A4R, B5, B5R, A5, A5R, B6R
Document Feeder Supported Media Weights	Single-sided scanning: 38 to 157 gsm (BW) Single-sided scanning: 64 to 157 gsm (CL) Double-sided scanning: 50 to 157 gsm (BW) Double-sided scanning: 64 to 157 gsm (CL)
Pull Scan Spec	Color Network ScanGear2. For both Twain and WIA Supported OS: Windows Vista/7/8/8.1/10 Windows Server 2008/Server 2008 R2/Server 2012/Server 2012 R2
Scan Resolution	100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi
Platen Acceptable Originals	Platen: Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2kg)] Feeder Size: A3, B4, A4, A4R, B5, B5R, A5, A5R, B6R
Scan Method	Send functionality available on all models. Scan to USB Memory Key: Available on all models Scan to Mobiles: A range of solutions are available to provide scanning to mobile devices. Please contact your sales representative for further information. TWAIN/WIA Pull scanning available on all models.
Scan Speed (A4)	Single-sided Scanning (BW): 80 ipm (300pi) / 80 ipm (600 dpi) Single-sided Scanning (CL): 80 ipm (300pi) / 60 ipm (600 dpi) Double-sided Scanning (BW): 160 ipm (300pi) / 150 ipm (600 dpi) Double-sided Scanning (CL): 160 ipm (300pi) / 80 ipm (600 dpi)

Send Specifications

Optional/Standard	Standard on all models
Destination	E-mail/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)
Colour Mode	Automatic-Colour Select (Full Colour/Grayscale), Automatic-Colour Select (Full Colour/Black-and-White), Full Colour, Grayscale, and Black-and-White
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Send Resolution	100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi
Communication Protocol	File: FTP, SMB v3.0, WebDAV E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)
File Format	Standard: TIFF, JPEG, PDF (Compact), XPS (Compact) Optional: PDF (Searchable, Apply policy, Optimise for Web, PDF A/1-b, Trace&Smooth, Encrypted), PDF/XPS (Digital Signature), XPS (Searchable), Office Open XML (PowerPoint, Word)
Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed

Fax Specifications

Optional/Standard	Optional on all models
Maximum Number of Connection Lines	4
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution	400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi
Sending/Recording Size	A5 and A5R* to A3 *Sent as A4
Fax Memory	Up to 30,000 pages
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 addresses
Memory Backup	Yes
Fax Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Select Line, Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed.

Store Specifications

Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes, 30,000 Maximum Pages Stored
Advanced Box	Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows Vista/7/8/8.1/10) Concurrent Connections (Max.): SMB: 64, WebDAV: 3 (Active Sessions)
Advanced Box Available Disc Space	Approx. 16GB (Standard HDD) Approx. 480GB (1TB HDD)
Advanced Box Features	Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support
Memory Media	Standard: USB Memory

Security Specifications

Authentication	Standard: User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in Optional: Universal Login Manager and uniFLOW
Data	Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated) Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)
Network	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP
Document	Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration Optional: Encrypted PDF, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scan locking

Environmental Specifications

Operating Environment	Temperature: 10 to 30 °C (50 to 86 °F) Humidity: 20 to 80 % RH (no condensation)
Power Requirements	iR-ADV 4551i: 220 - 240V (±10 %), 50/60 Hz (±2 Hz), 5.6Amp iR-ADV 4545i/4535i: 220 - 240V (±10 %), 50/60 Hz (±2 Hz), 5.2Amp iR-ADV 4525i: 220 - 240V (±10 %), 50/60 Hz (±2 Hz), 4.3Amp
Power Consumption	Maximum: 1.5 kW Standby: Approx. 37 W* *Reference Value Sleep mode: Approx. 0.9 W** ** 0.9W sleep mode is not available in all circumstances due to certain settings. Typical Electricity Consumption (TEC) rating: 2.6 kWh (iR-ADV 4551i) 2.3 kWh (iR-ADV 4545i), 1.8 kWh (iR-ADV 4535i), 1.1 kWh (iR-ADV 4525i)
Standards	ENERGY STAR® Qualified, Rated EPEAT (Gold), Blue Angel

Consumables

Toner	NPG-73 TONER BK (Toner Yield (Estimated @5% Coverage))

Software and Printer Management

Remote Management Tools	iW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management) eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance) Content Delivery System: Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web-based interface to each device that helps to provide remote device management and control.
Scanning Software	Network ScanGear: TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device.
Platform	MEAP (Multifunctional Embedded Application Platform): A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device. MEAP Web: Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services
Document Publishing	iW Desktop: Powerful print publishing software which easily combines documents from different sources and file formats, applies finishing with preview and templates to create professional looking documents. Includes PDF creation, annotation and compression capabilities for simple digital workflows such as proofing and authorisation.

Paper Supply Options

Name	Cassette Feeding Unit-AN1
Paper Capacity	550 sheets x 2 (80 gsm)
Paper Size	Standard: A3, B4, A4, A4R, B5R, B5, A5R Custom Size: 139.7 mm x 182.0 mm to 297.0 mm to 431.8 mm
Paper Weight	60 to 128 gsm
Power Source	From the Main Unit
Dimensions (W x D x H)	565 mm x 650 mm x 248 mm (When attached with the Main Unit)
Weight	Approx. 23.5 kg
Name	High Capacity Cassette Feeding Unit-B1
Paper Capacity	2,450 sheets (80 gsm)
Paper Size	A4
Paper Weight	60 to 128 gsm
Power Source	From the Main Unit
Dimensions (W x D x H)	565 mm x 650 mm x 248 mm (When attached with the Main Unit)
Weight	Approx. 28 kg
Name	Paper Deck Unit-F1
Paper Capacity	2,700 sheets (80 gsm)
Paper Size	A4, B5
Paper Weight	60 to 128 gsm
Power Source	From the Main Unit
Dimensions (W x D x H)	400 mm x 630 mm x 440 mm
Weight	Approx. 31 kg

Output Options

Name	Inner 2Way Tray-L1
Number of Trays	2
Total Output Capacity	Upper Tray: 100 sheets Lower Tray: 250 sheets
Paper Weight	52 to 220 gsm
Paper Size	Standard: A3, B4, A4, A4R, B5, B5R, A5R Envelope: No.10 (COM10), Monarch, DL, ISO-C5 Custom Size: 98 mm x 148 mm up to 297 mm x 431.8 mm
Dimensions (W x D x H)	426 mm x 413 mm x 109 mm (When attached with the Main Unit)
Weight	Approx. 0.77 kg
Name	Inner Finisher-J1 (Internal)
Number of Trays	2
Upper Capacity (Tray A)	A4, B5, A5R: 45 sheets A3, B4, A4R, B5R: 45 sheets
Lower Capacity (Tray B)	A4, B5, A5R: 500 sheets A3, B4, A4R, B5R: 250 sheets
Paper Weight	52 to 220 gsm
Staple Position	Corner, Double
Staple Capacity	Corner and Double Stapling: A4/B5: 50 sheets (52 to 90 gsm) A3/B4/A4R: 30 sheets (52 to 90 gsm) Eco Staple: A3/A4/B4/B5: 5 sheets (52 to 64 gsm) 4 sheets (65 to 81.4 gsm), 3 sheets (81.5 to 105 gsm) Staple On Demand: 40 sheets (80 gsm)
Dimensions (W x D x H)	604 mm x 535 mm x 205 mm (When the extension tray is extended)
Weight	Approx. 7.2 kg
Name	Staple Finisher-Y1 (External)
Number of Trays	2
Upper Capacity (Tray A)	A4, B5, A5R: 250 sheets A3, B4, A4R, B5R: 125 sheets
Lower Capacity (Tray B)	A4, B5, A5R: 3,000 sheets A3, B4, B5R, A4R: 1,500 sheets
Paper Weight	Upper Tray: 52 to 220 gsm Lower Tray: 52 to 220 gsm
Staple Position	Corner, Double
Staple Capacity	Corner and Double Stapling: A4/B5: 50 sheets (52 to 90 gsm) A3/B4/A4R: 30 sheets (52 to 90 gsm) Eco Staple: A3/A4: 5 sheets (52 to 64 gsm) 4 sheets (65 to 81.4 gsm), 3 sheets (81.5 to 105 gsm) Staple On Demand: 50 sheets (90 gsm)
Dimensions (W x D x H)	637 mm x 623 mm x 1,142 mm (When the extension tray is extended)
Weight	Approx. 31 kg
Name	Booklet Finisher-Y1 (External)
Number of Trays	2
Upper Capacity (Tray A)	A4, B5, A5R: 250 sheets A3, B4, A4R, B5R: 125 sheets
Lower Capacity (Tray B)	A4, B5, A5R: 3,000 sheets A3, B4, B5R, A4R: 1,500 sheets
Paper Weight	Upper Tray: 52 to 220 gsm Lower Tray: 52 to 220 gsm
Staple Position	Corner, Double
Staple Capacity	Corner and Double Stapling: A4/B5: 50 sheets (52 to 90 gsm) A3, B4, A4R: 30 sheets (52 to 90 gsm) Eco Staple: A3/A4: 5 sheets (52 to 64 gsm) 4 sheets (65 to 81.4 gsm), 3 sheets (81.5 to 105 gsm) Staple On Demand: 50 sheets (90 gsm)
Booklet Stitch Paper Size	Standard: A3, B4, A4R, Custom Size: 195.0 mm x 270 mm to 297 mm x 431.8 mm
Booklet Stitch Staple Capacity	20 sheets x 10 sets (81 gsm) (including 1 cover sheet up to 220 gsm)
Dimensions (W x D x H)	637 mm x 623 mm x 1,142 mm (When the extension tray is extended)
Weight	Approx. 57 kg
Name	Inner 2/3 Hole Puncher-C1, Two or Three Holes (Requires the Inner Finisher-J1)
Acceptable Punch Paper Weight	52 to 220 gsm
Acceptable Punch Paper Size	Two holes: A3, B4, A4, A4R, B5, B5R Three holes: A3, B4, A4, B5
Power Source	From the Main Unit
Name	Inner 2/F4 Hole Puncher, Two or Four Holes (Requires the Inner Finisher-J1)
Acceptable Punch Paper Weight	52 to 220 gsm
Acceptable Punch Paper Size	Two holes: A3, B4, A4, A4R, B5, B5R Four holes: A3, A4
Power Source	From the Main Unit
Name	2/3 Hole Puncher Unit-A1, Two or Three Holes (Requires either the Staple Finisher-Y1 or Booklet Finisher-Y1)
Acceptable Punch Paper Weight	52 to 220 gsm
Acceptable Punch Paper Size	Two holes: A3, B4, A4, A4R, B5, B5R Three holes: A3, B4, A4, B5
Power Source	From the Main Unit
Name	2/4 Hole Puncher Unit-A1, Two or Four Holes (Requires either the Staple Finisher-Y1 or Booklet Finisher-Y1)
Acceptable Punch Paper Weight	52 to 220 gsm
Acceptable Punch Paper Size	Two holes: A3, B4, A4, A4R, B5, B5R Four holes: A3, A4
Power Source	From the Main Unit
Name	4 Hole Puncher Unit-A1, Four Holes (Requires either the Staple Finisher-Y1 or Booklet Finisher-Y1)
Acceptable Punch Paper Weight	52 to 220 gsm
Acceptable Punch Paper Size	Four holes: A3, B4, A4, A4R, B5, B5R
Power Source	From the Main Unit

Hardware Accessories

Card Readers	MiCard Plus Proximity Card Reader, Copy Card Reader-F1, Copy Card Reader Attachment-B5
Others	Envelope Feeder Attachment Kit-D1, Utility Tray-B1

Security Options

Document Security	Document Scan Lock Kit-B1, Secure Watermark-B1, Encrypted Secure Print Software-D1, iR-ADV Security Kit-K1 for IEEE 2600.1 Common Criteria Certification
Data Security	HDD Mirroring Kit-J1, 2.5inch/250GB HDD-N1, 2.5inch/1TB HDD-P1, Removable HDD Kit-AL1

System and Controller Options

Print Accessories	PCL International Font Set-A1
Barcode Printing	Barcode Printing Kit-D1
System Accessories	Web Access Software-K1, Serial Interface Kit-K3
Fax Accessories	Super G3 Fax Board-AS1, Super G3 2nd Line Fax Board-AS1, Super G3 3rd/4th Line Fax Board-AS1, IP Fax Expansion Kit-B1

Other Options

Accessibility Accessories	ADF Access Handle-A1, Voice Guidance Kit-G1, Voice Operation Kit-D1
Consumables	Stamp Ink Cartridge-C1, Staple-P1, Staple Cartridge-Y1

Canon

canon.com.au/business
1800 444 199

No one does it like you