COMPACT AND **SMART**

Canon imageRUNNER ADVANCE
400i / 500i



Suitable for busy workgroups and departments, these compact imageRUNNER ADVANCE devices offer efficient mono output and intelligent document handling to optimise your workflows, save you money and secure your confidential information.

Productivity

- Unrivalled and consistent user experience through a large 17.8cm tiltable colour touch screen and intuitive menus
- Unique personalisation capabilities simplify and automate commonly performed tasks by user
- Colour duplex scanning and sending with native support for data formats such as searchable PDF and Open Office XML (Powerpoint) enables re-use and re-purpose of digital content
- Integration with powerful document, capture and output management solutions provide process optimisation
- Up to 2,300 sheet paper capacity for busy workgroups and departments
- Time-saving automatic staple finishing option
- Support for mobile working.

Device and Information Security

- Award-wining and smart user authentication ensures control without impacting on user productivity or convenience
- Ability to disable functions by user to prevent unauthorised usage
- A variety of standard features such as data erase, IP and MAC address filtering and IPSec protects the device and network data transfer
- An extensive range of options offer compliance to highest levels covering all aspects of information security.

Cost Control

- The functionality of many devices in one compact multifunctional device
- Efficient and reliable monochrome output for workgroups and departments
- Apply policies and restrict usage at function level by user
- Efficient device monitoring, reporting and diagnostics for easy management and maintenance
- Ability to use shared resources, such as fax and Advance Space, from other iR-ADV devices.

Integration

- Versatile imageRUNNER ADVANCE portfolio addresses the needs of all workplaces from small workgroups through to large departments and Corporate Reprographic Departments
- Native support for industry and network standards i.e. Genuine Adobe PostScript and PCL ensures hassle-free integration with ERP, CRM and other business information systems
- Consistent imageRUNNER ADVANCE platform and portfolio simplifies management and operation across a fleet
- Canon's powerful embedded MEAP & MEAP Web platform provides a strong link to a range of award-winning document, capture and output management solutions for process optimisation
- Easily configure, manage and upgrade your device, whether individually, or as part of a larger fleet using Canon's device management tools
- Shared resources across the network.

At a glance

- 40–50 ppm mono
- imageRUNNER ADVANCE platform
- Space saving, modular design
- 17.8cm colour tiltable touch screen
- Up to 2300 sheet capacity
- Up to A4 output
- Automatic staple finishing option

Sustainability

- Class leading Typical Electricity Consumption (TEC)* ratings
- Consumes as little as 1W in sleep mode
- Incorporates recycled materials and bio-plastics
- ENERGY STAR® qualified.

Canon

No one does it like you

imageRUNNER ADVANCE 400i / 500i

Printer Specifications

Machine type	Monochrome A4 Laser Multifunctional (Reader/Printer standard)
Available Core functions	Print, Copy, Scan, Send and optional Fax
Print speed (BW)	iR-ADV 400i: Up to 40 ppm (A4 Single-sided), 25ppm (A5 Single-sided), 39ppm (A4 Double-sided), 22ppm (A5 Double-sided) iR-ADV 500i: Up to 50 ppm (A4 Single-sided), 25ppm (A5 Single-sided), 49ppm (A4 Double-sided), 22ppm (A5 Double-sided)
Printing method	Monochrome Laser Beam Printing
Print resolution	1200 dpi x 1200 dpi, 600 dpi x 600 dpi
Double sided printing	Automatic (Standard)
Printing from memory media	Direct printing available from USB memory key, Remote UI and Web Access* Supported file types: JPEG, TIFF, PDF, XPS** (* XPS print from websites is not supported) (** XPS requires DIRECT PRINT KIT (XPS)-H1)
Printing from mobiles or internet-connected devices and cloud-based services	A range of software and MEAP-based solutions is available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.
Paper input (Standard)	1 x 550-sheet (80 gsm) cassette, 100-sheet (80 gsm) multi-purpose tray
Paper input (Option)	Up to 3 x 550-sheet cassettes (80 gsm) (Cassette Module-AA1)
Maximum paper input capacity	2300 sheets (80 gsm)
Paper output capacity	Without Finisher: 250 sheets (80 gsm) With Staple Finisher: 500 sheets without stapling (80gsm), 20 sets with stapling
Finishing capabilities	Standard: Group Optional Staple Finisher: Collate, Group, Staple Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Prepunched paper, Bond, Transparency, Label, Letterhead, Bond paper, Envelope
Supported media types	Cassette/s: Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Envelope* *Envelope support via drawer 2 only. Requires optional Envelope Cassette-E1 Multi-purpose tray: Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Bond, Transparency, Label, Envelope (No.10 (COM10), Monarch, ISO-C5, DL)
Supported media sizes	Paper Drawer 1, 3 and 4: Standard size: A4, A5, B5, Legal, Letter, Executive, Statement Paper Drawer 2: Standard size: A4, A5, B5, Legal, Letter, Executive, Statement, Envelopes* (No.10 (COM10), Monarch, ISO-C5, DL) *Requires optional Envelope Cassette-E1 Multi-purpose tray: Standard size: A4, A5, B5, Legal, Letter, Executive, Statement, Custom size (99 mm to 216 mm × 140 mm to 356 mm), Envelopes (No.10 (COM10), Monarch, ISO-C5,DL)
Supported media weights	Cassette/s: 64 to 105 g/m^2, Multi-purpose tray: 64 to 128 g/m^2, Duplex: 64 to 105 g/m^2
Page Description Language(s)	UFRII , PCL5e/6, Adobe PostScript Level 3 (Standard on all models)
Fonts	PCL fonts: 93 Roman, 10 Bitmap, 2 OCR fonts, Andale 4, PS fonts: 136 Roman fonts
Operating System compatibility	UFRII: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008R2/ Windows 8/Server 2012, MAC OS X (10.5.8 or later) PCL: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008 R2/ Windows 8/Server 2012 PS: Windows XP/Server 2003/Vista/Server 2008/Windows 7/Server 2008 R2/ Windows 8/Server 2012, MAC OS X (10.5.8 or later) PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows 2000/Windows XP/Windosw Vista/Windows 7/Windows 8 Please refer to http://software.canon-europe.com/ for availability of print solutions for other operating systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place.

Copy Specifications

Copy speed	iR-ADV 500i: Up to 50 ppm (A4), iR-ADV 400i: Up to 40 ppm (A4)
First Copy Output Time (FCOT)	Approx. 5.0 seconds or less
Copy resolution	Reading: 600 dpi x 600 dpi Printing: 1200 dpi x 1200 dpi for characters/lines, 600 dpi x 600 dpi for graphics/images
Multiple copy	Up to 999 copies
Reduction/Enlargement	Zoom: 25-400 % in 1 % increments Fixed Zoom Ratio: 25 %, 50 %, 70 %, 100 %, 141 %, 200 %, 400 %

Scan Specifications

Optional/Standard	Standard on all models
Supported media size/s	A4, A5, B5, Custom sizes (W x L): Min. 140 mm x 140 mm, Max. 356 mm x 216 mm
Supported media weight/s	Single-sided scanning: 42 to 128 gsm/64 to 128 gsm (Mono/Colour), Double-sided scanning: 50 to 128 gsm/64 to 128 gsm (Mono/Colour)
Scan resolution	Mono Scan: 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi, 400 dpi, 600 dpi Colour Scan: 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi
Double sided scanning	2-sided to 2-sided (Automatic)
Scan speed (A4, 300 dpi)	Mono single-sided: 50 ipm/A4(600dpi/300dpi) Mono double-sided: 32 ipm/A4(600dpi/300dpi) Colour single-sided: 50 ipm/A4(300dpi) Colour double-sided: 32 ipm/A4(300dpi)
Scan methods	Push Scan: Colour Universal Send functionality is standard. Integration with a range of optional MEAP-based capture software adds powerful worflow and conversion capabilties. Please contact your sales representative for further information. Pull Scan: TWAIN/WIA Pull scanning available on all models. Scan to USB Memory Key Scan to Mobiles, internet-connected devices and cloud-based services: A range of solutions is available to provide scanning to mobile devices, internetconnected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.
Pull scan specifications	TWAIN via Network TWAIN Driver (Colour Network ScanGear) Supported OS: Windows 2000/Windows XP/Windows Server 2003/Windows Vista/Windows Server 2008/ Windows 7/Windows 8 (32 bit, 64 bit in compatibility mode)* WIA via Network WIA Driver Supported OS: Windows Vista/Windows Server 2008/Windows 7/Windows 8 (32 bit, 64 bit)* *The drivers are available via http://software.canon-europe.com/

Send Specifications

Optional/Standard	Standard on all models
Send resolution	100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi, 400 dpi, 600 dpi
Destinations	E-Mail/Internet FAX (SMTP), Fax(option), PC (SMB, FTP, WebDAV), Google Drive with Cloud Connect for iR-ADV MEAP application
Address Book/Speed dials	LDAP(Max. 2000 searchable), Local (Max. 1800 including 200 Speed dials)
File formats	TIFF, JPEG, PDF, XPS, PDF/XPS (compact), PDF/A-1b, Searchable PDF/XPS, Office Open XML (PowerPoint)
Optional Universal Send Feature Sets	UNIVERSAL SEND ADVANCED FEATURE SET-E1, UNIVERSAL SEND SECURITY FEATURE SET-D1, UNIVERSAL SEND DIGITAL USER SIGNATURE KIT-C1

Fax Specifications

Optional/Standard	Optional on all models (requires SUPER G3 FAX BOARD-AM1)
Modem speed	Super G3 33.6kbps (Up to 3 seconds per page (see [1]))
Fax resolution	Standard: 200 x 100 dpi, Fine: 200 x 200 dpi, Super fine: 200 x 400 dpi, Ultra fine: 400 x 400 dpi
FAX memory	Up to 6000 pages (see [1])
Speed dials	Max. 200
Group dials/destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses
Memory backup	Yes (Approx. 3 hours)
Other features	Fax Forwarding, Dual Access, PC Fax (TX only)

General Specifications

Warm-up Time	Approx. 34 seconds from power ON (Normal mode), 10 seconds from power ON (Quick Start mode)
Recovery from sleep mode	10 seconds or less
Interface type	USB 2.0 Hi-Speed,1000BaseT/100Base-TX/10Base-T, 1 x USB Host (Front), 2 x USB Host(Rear)
Network protocols	TCP/IP* (LPD/Port 9100/WSD/IPP/IPPS/SMB/FTP), IPX/SPX (NDS, Bindery), AppleTalk *IPv4/IPv6 support Recommended third party wireless solution is Silex SX-2500CG. For more details please refer to www.silex-europe.com
Processor Speed	1.66 Ghz
Memory	1.5 GB
Hard Disk Drive	160 GB Hard Disk Drive (Usable space 80 GB)
Control panel	17.8 cm (7 inch) WVGA Colour TFT LCD Touch & Tiltable Panel
Dimensions (W x D x H)	560 mm x 567 mm x 633 mm (standard), 560 mm x 567 mm x 752 mm (with 1 optional cassette), 560 mm x 567 mm x 868 mm (with 2 optional cassettes), 560 mm x 567 mm x 984 mm (with 3 optional cassettes)
Installation space (W x D)	787 mm x 567 mm (Main unit + Multi-purpose tray open + Cassette drawers closed) 1182 mm x 567 mm (Main unit + Staple Finisher + Multi-purpose tray open + Cassette drawers closed)
Weight	47.9kg excluding Toner
Operating environment	Temperature: 10 to 30°C (50 to 86°F), Humidity: 20 to 80 % RH (no condensation)
Power Source	220-240 V (±10 %), 50/60 Hz (±2 Hz), 4.3-5.6 Amp
Power Consumption	Maximum: Approx. 1.6 KW Standby: Approx. 53.72 W Sleep mode: Approx. 1 W or less (see [2]) Typical Electricity Consumption (TEC) rating (see [3]): 2.4 kWh (iRADV 500i) / 1.873 kWh (iR-ADV 400i)
Noise Levels	Sound Pressure (see [4]) Active: 75 dB or less (iR-ADV 500i), 73 dB or less (iR-ADV 400i) Standby: 53 dB or less
Security Features	Standard: IP/Mac Address Filtering, IPSEC, SNMP V3.0, IEEE 802.1X, Trusted Platform Module (TPM), Secure Print, HDD Password Lock, Data Erase, Universal Login Manager, Department ID, SSO-H, Access Management System. Optional: Encrypted Secure Print, Encrypted PDF, HDD Encryption, User and Device signatures, Secure Watermarks, MailboxLite.

Consumables

Toner bottle	C-EXV 43 Black Toner (Yield: 15200 pages (see [5]))

Other options

	Staple Finisher-R1. Number of Trays: 1. Stack Capacity: With stapling: 20 sets. Without stapling: 500 sheets. Maximum Stapling capacity: Up to 50 sheets. Paper Weight: 64 to 128 g/m^2. Staple Position: Single (Top-Left). Dimensions (W x D x H): 798 mm × 395 mm × 263 mm Weight: Approx. 10.5 kg.
Cassette module	Cassette Module-AA1 Description: Optional cassette module with 550 sheets paper capacity. Up to 3 cassette units can be added to a main unit. Dimensions (W x D x H): 540 mm x 500 mm x 119 mm. Weight: Approx. 7.7 kg
Hardware accessories 1	Plain Pedestal PEDADV6 (Height of Pedestal: 110 mm) Plain Pedestal PEDADV7 (Height of Pedestal: 343 mm) Envelope Cassette -E1
Print controller accessories	BARCODE PRINTING KIT-D1
System accessories	WEB ACCESS SOFTWARE-J1 SUPER G3 FAX BOARD-AM1 Super G3 2ND LINE FAX BOARD-AM1 REMOTE FAX KIT IC CARD READER BOX-A1
Device security accessories	HDD DATA ENCRYPTION KIT-C6
Document security accessories	SECURE WATERMARK-B1 ENCRYPTED PRINTING SOFTWARE-D1
Accessibility accessories	ADF ACCESS HANDLE-A1 REMOTE OPERATORS SOFTWARE KIT-B1
Other options	STAPLE-P1: Plain staples for Staple Finisher-R1

[1] Based on ITU-T Standard Chart No.1
[2] 1 watt sleep mode may not be possible in all circumstances. Certain network configurations and options may prevent the device from entering deep sleep mode. Please refer to the user guide for more information.
[3] Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-houes (kWh). The test methodology is defined by Energy Star (http://www.eu-energystar.org).
[4] Declared noise emission in accordance with ISO 7779
[5] Based on 6% coverage (A4)

All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon

canon.com.au/business
1800 444 199

No one does it like you