LEAVE DIGITAL TRANSFORMATION TO THE *NEXT GENERATION*

Canon imageRUNNER ADVANCE

C5500i Series



The imageRUNNER ADVANCE C5500i Series delivers operational efficiency through streamlining document workflows and an intuitive, personalised user experience. Transform your business for organisational mobility with the Gen III platform, designed to be the core of digital communications where imaging technology, cloud connectivity and mobile solutions seamlessly converge.

- Print up to 60 ppm in black & white and colour
- Scan up to 160/160 ipm
- Print up to SRA3
- 6,350-sheet paper capacity

PERFORMANCE

Save time and resources with increased workflow productivity

- Intuitive, user-friendly interface with a large 10.1 WSVGA touchscreen and smart phone similarities
- My ADVANCE functions allow users to create their own personalised experience, tailored to meet their unique needs
- Streamline digital workflows with improved scanning abilities such as single-pass document feeder, automatic blank page removal, scan and convert to searchable PDF, and Microsoft Word and PowerPoint files
- High quality output systems with V2 colour imaging technology and a range of finishing options including stapling, booklet, staple on-demand and eco staple

COST CONTROL

Manage costs with ease thanks to improved efficiencies

- Reduce wastage with Forced Job Hold at the device allowing users to preview, change print settings and sample print before releasing the full job
- Manage print by applying print policies and monitoring output
- Control print costs by restricting access not only to the device but to functions by user such as colour and 1-sided printing
- Reduce downtime and use of IT resources with remote support and fleet management

INTEGRATION

Seamlessly integrate into new and existing systems

- Leverage Canon's MEAP platform to optimise processes integrating with a range of powerful document, capture and output management solutions
- Collaborate with key line of business applications and external systems

MOBILITY

Organisational mobility allows for an innovative way of working, keeping users connected on the go

- Simple and easy mobile connectivity with in-built wifi
- Flexible mobile workflows enable users to intuitively print, scan and capture directly on their mobile with Canon PRINT Business
- Support for Apple AirPrint, Mopria and Google Cloud

Canon

No one does it like you

SUSTAINABILITY

Achieve environmental goals by incorporating responsible design and efficient operations

- Motion Sensor and Sleep Recovery Triggers reduce energy consumption
- Sustainable design introduced with recycled materials and bio-based plastics
- Minimise waste with default print settings including two-sided, and black and white options
- ENERGY STAR and Blue Angel qualified with leading-class, Typical Electricity Consumption (TEC) rating

SECURITY

Safeguard data and ensure sensitive information remains secure

- Control who has device access with user authentication systems
- Ensure data is secure with hard drive encryption
- IPsec, port filtering capabilities and SSL technology keeps information private and secure throughout your network

CONFIGURATION

Booklet Finisher

- 2-tray, 3,250 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-Demand 50 sheets (80 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers



Staple Finisher

- 2-tray, 3,250 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-Demand 50 sheets (80 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers





Inner 2 Way Tray

- Separates copies, prints and faxes
- Adds a second internal output tray



Buffer Pass Unit

- Transports paper to external finisher




Inner Finisher

- 1-tray, 550 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-Demand 45 sheets (80 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers





Utility Tray



Copy Tray



Paper Deck Unit

- Supports A4
- Media weight 52-256 gsm
- 2,700 sheets (80 gsm)



ColorPASS-GX500

- PS/APPE
- 4GB/1TB
- Fiery FS200 Pro



imagePASS-PS1

- PCL/PS
- 2GB/500GB
- Fiery FS200

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalised printing with the built-in, entry-level Fiery FreeForm™ or with the supported industry-leading variable data printing (VDP) formats
- Integrates print production workflows with EFI™ management information systems, Web-to-Print systems, and popular pre-press workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules C5550i and C5560i only



Cassette Feeding Unit

- Supports up to A3
- Media weight 52-256 gsm
- 2 x 550 sheets (80 gsm)



High Capacity Cassette Feeding Unit

- Supports A4
- Media weight 52-256 gsm
- 2,450 sheets (80 gsm)

imageRUNNER ADVANCE C5500i Series

Main Unit

Type	Colour Laser Multifunctional
Core Function	Print, Copy, Scan, Send, Store and Optional Fax
Processor	Canon Dual Custom Processor (Shared)
Control Panel	25.6 cm (10.1 inch) TFT LCD WSVGA Colour Touch panel
Memory	Standard: 4GB RAM
Hard Disk Drive	Standard: 250GB Maximum: 1TB
Mirroring Hard Disk Drive	Optional: 250GB, 1TB
Interface Connection	Network: Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) Optional: NFC, Bluetooth Others: Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device) Optional: Serial Interface, Copy Control Interface
Paper Capacity (80gsm)	Standard: 1,200 Sheets Maximum: 6,350 Sheets
Paper Sources (80gsm)	Standard: Two 550-sheet Paper Cassettes 100-sheet Multi-purpose tray Optional: Dual 550-sheet Paper Cassettes (Cassette Feeding Unit-AM1), 2,450-sheet Paper deck (High Capacity Cassette Feeding Unit-A1), 2,700-sheet Paper deck (Paper Deck Unit-F1)
Paper Output Capacity (80gsm)	Standard: 250 Sheets Maximum: 3,450 Sheets (with External Finisher and Copy Tray)
Finishing Capabilities	Standard: Collate, Group With Inner Finisher : Collate, Group, Offset, Staple, *Hole Punch, Eco Staple, Staple On Demand With External Finisher : Collate, Group, Offset, Staple, **Booklet, *Hole Punch, Eco Staple, Staple On Demand * Necessary for Inner 2/3 Hole Puncher-B1 or Inner 2/4 Hole Puncher-B1 * Necessary for 2/3 Hole Puncher Unit-A1 or 2/4 Hole Puncher Unit-A1 **Booklet Finisher-Y1 only
Supported Media Types	Cassettes 1: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency, Bond paper, Envelope, Letterhead Cassettes 2: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency, Tab paper, Bond paper, Envelope, Letterhead Cassettes 3/4 (Cassette Feeding Unit-AM1): Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency, Bond paper, Letterhead Cassette Deck (High Capacity Cassette Feeding Unit-A1): Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Bond paper, Letterhead Multi-purpose tray: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency, Tracing paper, Label, Tab paper. Bond paper, Coated paper, Envelope, Letterhead Paper Deck Unit-F1: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Bond paper, Letterhead
Supported Media Sizes	Cassette 1: Standard size: A4, B5, A5, A5R Custom Size : 98.0 mm x 148 mm to 297 mm x 215.9 mm Cassette 2: Standard size: A3, B4, A4, A4R, B5, B5R, A5R Custom size: 98.0 mm x 182 mm to 304.8 mm x 457.2 mm Cassette 3/4 (Cassette Feeding Unit-AM1): Standard size: A3, B4, A4, A4R, B5, B5R, A5R Custom size: 98.0 mm x 182 mm to 304.8 mm x 457.2 mm Cassette Deck (High Capacity Cassette Feeding Unit-A1): Standard size: A4 Multi-purpose tray: Standard size: A3, B4, A4, A4R, B5, B5R, A5, A5R, SRA3, Envelope (No.10(COM10), Monarch, DL, ISO-C5), Envelope Custom Size (98.0 mm x 98.4 mm to 320 mm to 457.2 mm) Custom Size : 98.0 mm x 139.7 mm to 320 mm x 457.2 mm Free Size: 98.0 mm x 139.7 mm to 320 mm x 457.2 mm Paper Deck Unit-F1: A4, B5
Supported Media Weights	Cassettes: 52 to 256 gsm Multi-purpose tray: 52 to 300 gsm Duplex: 52 to 220 gsm
Warm-up Time	From Power On: 30 Seconds or Less From Deep Sleep Mode: 10 Seconds or Less
Dimensions (W x D x H)	620 mm x 742 mm x 950 mm
Installation Space (W x D)	943 mm x 1,176 mm (when Multi-purpose tray Extended + Cassette Drawers open)
Weight*	Approx. 143kg *Including the toner bottle

Print Specifications

Printing Method	Colour laser
Print Speed	iR-ADV C5560i: 60 ppm (A4) 32 ppm (A3) iR-ADV C5550i: 50 ppm (A4) 27 ppm (A3) iR-ADV C5540i: 40 ppm (A4) 22 ppm (A3) iR-ADV C5535i: 35 ppm (A4) 18 ppm (A3)
Print Resolution*	600 dpi x 600 dpi (Default), 1,200 dpi x 1,200 dpi (Up to) *Data processing resolution
Page Description Languages	UFR II, PCL6 (Standard) Adobe PS 3 (Optional)
Double Sided Printing	Automatic (Standard)
Direct Print	Direct printing available from USB memory key, Advanced box, Remote UI and Web Access (Only PDF print from websites is supported) Supported File Types: PDF, TIFF, JPEG, EPS, XPS
Fonts	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T* (Japanese, Korean, Simplified and Traditional Chinese) , Barcode fonts** *Requires optional PCL International Font Set-A1 **Require optional Barcode Printing Kit-D1 PS fonts: 136 Roman
Operating System	UFRII: Server 2003/Server 2003 R2/Windows Vista/Server 2008/Windows 7/ Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2 Windows 10, MAC OS X (10.6.8 or later) PCL: Server 2003/Server 2003 R2/Windows Vista/Server 2008/Windows 7 Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2 Windows 10 PS: Server 2003/Server 2003 R2/Windows Vista/Server 2008/Windows 7/ Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2 Windows 10, MAC OS X (10.6.8 or later) PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows Vista/Windows 7 Windows 8/Windows8.1/Windows10

Copy Specifications

Copy Speed	iR-ADV C5560i: 60 ppm (A4), 32 ppm (A3) iR-ADV C5550i: 50 ppm (A4), 27 ppm (A3) iR-ADV C5540i: 40 ppm (A4), 22 ppm (A3) iR-ADV C5535i: 35 ppm (A4), 18 ppm (A3)
*First-Copy-Out Time (A4)	iR-ADV C5560i: Approx. 2.9 seconds or less (BW), Approx. 4.5 seconds or less (CL) *: 20 °C to 30 °C Environment iR-ADV C5550i: Approx. 3.5 seconds or less (BW), Approx. 5.2 seconds or less (CL) *: 20 °C to 30 °C Environment iR-ADV C5540i: Approx. 4.1 seconds or less (BW), Approx. 6.1 seconds or less (CL) *: 20 °C to 30 °C Environment iR-ADV C5535i: Approx. 4.9 seconds or less (BW), Approx. 7.4 seconds or less (CL) *: 20 °C to 30 °C Environment
Copy Resolution	Reading: 600 dpi x 600 dpi Printing: Up to 1,200 dpi x 1,200 dpi (Data processing resolution)
Copy Exposure	Automatic or Manual (11 Levels)
Magnification	25% - 400% (1% Increments)
Preset Reductions	25%, 50%, 61%, 70%, 81%, 86%
Preset Enlargements	115%, 122%, 141%, 200%, 400%

Scan Specifications

Type	Colour Platen and Single-pass Duplexing Automatic Document Feeder
Document Feeder Paper Capacity	150 Sheets (80gsm)
Document Feeder Supported Media Sizes	A3, A4, A4R, A5, A5R, B4, B5, B5R, B6R
Document Feeder Supported Media Weights	Single-sided scanning: 38 to 157 gsm (BW) Single-sided scanning: 64 to 157 gsm (CL) Double-sided scanning: 50 to 157 gsm (BW) Double-sided scanning: 64 to 157 gsm (CL)
Pull Scan Spec	Colour Network ScanGear2. For both Twain and WIA Supported OS: Windows Vista/7/8/8.1/10 / Windows Server 2003/Server 2003 R2 Server 2008/ Server 2008 R2/Server 2012/Server 2012 R2
Scan Resolution	100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi
Platen Acceptable Originals	Platen: Sheet, Book, 3-Dimensional Objects [Up to 2kg] Feeder size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6
Scan Speed (A4)	Single-sided Scanning (BW) : 80 ipm (300pi) / 80 ipm (600 dpi) Single-sided Scanning (Colour) : 80 ipm (300pi) / 60 ipm (600 dpi) Double-sided Scanning (BW) : 160 ipm (300pi) / 150 ipm (600 dpi) Double-sided Scanning (Colour) : 160 ipm (300pi) / 80 ipm (600 dpi)
Double Sided Scanning	2-sided to 2-sided (Automatic)

Send Specifications

Optional/Standard	Standard on all models
Destination	E-mail/Internet FAX (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 FAX(Optional), IP Fax(Optional)
Colour Mode	Automatic-Colour Select (Full Colour/Grayscale), Automatic-Colour Select (Full Colour/Black-and-White), Full colour, Grayscale, and Black-and-White
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Send Resolution	100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi
Communication Protocol	File: FTP, SMB , WebDAV E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)
File Format	Standard: TIFF, JPEG, PDF(Compact, Apply policy, Optimise for Web, PDF A/1-b), XPS(Compact) Optional: PDF(Searchable, Trace&Smooth, Encrypted), PDF/XPS (Digital Signature), Office Open XML (PowerPoint, Word), XPS(Searchable)

Fax Specifications

Optional/Standard	Optional on all models
Maximum Number of Connection Lines	4
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution	400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi
Sending/Recording Size	A5 and A5R* to A3 *Sent as A4
FAX Memory	Up to 30,000 pages
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 addresses
Memory Backup	Yes

Store Specifications

Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes, 30,000 Maximum Pages Stored
Advanced Box	Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows Vista/7/8/8.1/10) Concurrent Connections (Max.): SMB: 64, WebDAV: 3 (Active Sessions)
Advanced Box Available Disc Space	Approx. 16GB (Standard HDD) Approx. 480GB (1TB HDD)
Memory Media	Standard: USB Memory

Security Specifications

Authentication	Standard: Picture Login Authentication, DepartmentID, Authentication, (Device and Function Level Log-in), Access Management System Optional: My Print Anywhere secure print (Requires uniFLOW)
Data	Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated) Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)
Network	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP
Document	Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration Optional: Encrypted PDF, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scan locking

Environmental Specifications

Operating Environment	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80 % RH (no condensation)
Power Requirements	220-240V(±10 %), 50/60Hz (±2 Hz), 6Amp
Power Consumption	Maximum: 1.8 kW Standby: Approx. 67.9 W* *Reference Value Sleep mode: Approx. 0.8 W ** ** 0.8W sleep mode is not available in all circumstances due to certain settings. Typical Electricity Consumption (TEC) rating[2]: 3.1 kWh (iR-ADV C5560i), 2.5 kWh (iR-ADV C5550i), 2.0 kWh (iR-ADV C5540i), 1.6 kWh (iR-ADV C5535i)
Standards	ENERGY STAR® Qualified, Rated EPEAT(Gold), Blue Angel

Consumables

Toner	NPG-71 TONER BK/C/M/Y, NPG-71L TONER C/M/Y

Software and Printer Management

Remote Management Tools	iW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management) eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance) Content Delivery System: Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web-based interface to each device that helps to provide remote device management and control.
Platform	MEAP (Multifunctional Embedded Application Platform): A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device. MEAP Web: Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services
Document Publishing	iW Desktop: Powerful print publishing software which easily combines documents from different sources and file formats, applies finishing with preview and templates to create professional looking documents. Includes PDF creation, annotation and compression capabilities for simple digital workflows such as proofing and authorisation.

Fiery Print Controller Specifications

Optional/Standard	Optional on all models
Name	imagePASS-P1 (Embedded)
Print Resolution	1200 dpi x 1200 dpi, 600 dpi x 600 dpi
Standard Page Description Languages	Adobe PS3, PCL6
Memory	2 GB
Hard Disk Drive	500 GB
Processor	Intel Celeron G1820 2.7GHz
System	Fiery FS200
Fonts	PS: 138 Fonts PCL: 113 Fonts
Supported Operating Systems	Windows VISTA 32 and 64 bit / Windows 7 / 32 and 64 bit / Windows 8 32 and 64 bit / Windows 8.1 32 and 64 bit / Windows 10 32 and 64 bit / Windows Server 2008 32 and 64 bit / Windows Server 2008 R2 64 bit only / Windows Server 2012 64bit only / Windows Server 2012 R2 64bit only / MAC OS (10.7,10.8,10.9,10.10,10.11)
Interface	2 x Ethernet (1000Base-T/100Base- TX/10Base-T), USB3.0 x 2 (Rear x 2), USB2.0 x 4 (Rear x 4)
Network Protocols	TCP/IP (LPR/ Port 9100/ SNMP / IPP / HTTP / HTTPs / SMB / FTP) / DNS
Fiery Print Controller Standard Features	Fiery Command WorkStation 5 / Paper Catalog / Fiery Spot-On / Fiery Remote Scan
Fiery Print Controller Options	Fiery Impose / Fiery Compose / Fiery Impose and Compose / Productivity Package Web Activate (Include Fiery JDF) Hot Folders License
Dimensions (W x D x H)	285 mm x 93 mm x 295 mm
Optional/Standard	Optional on imageRUNNER ADVANCE C5560i/C5550i
Name	ColorPASS-GX500 (External)
Print Resolution	1200 dpi x 1200 dpi, 600 dpi x 600 dpi
Page Description Languages	Adobe PS 3, PCL5(Driverless)
Memory	4 GB
Hard Disk Drive	1 TB
Processor	Intel Core i5-4570S 2.9 GHz up to 3.6 GHz w/ Turbo
System	Fiery FS200 Pro
	PS: 138 Fonts PCL: 113 Fonts
Supported Operating Systems	Windows VISTA 32 and 64 bit / Windows 7 32 and 64 bit / Windows 8 32 and 64 bit / Windows 8.1 32 and 64 bit / Windows 10 32 and 64 bit / Windows Server 2008 32 and 64 bit / Windows Server 2008 R2 64 bit only / Windows Server 2012 64bit only / Windows Server 2012 R2 64bit only / MACOS (10.7,10.8,10.9,10.10,10.11)
Interface	2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB3.0 x 6 (Front x 2, Rear x 4), USB2.0 x 2 (Front x 2)
Network protocols	TCP/IP (LPR/ Port 9100/ SNMP / IPP / HTTP / HTTPs / FTP / SMB) / DNS
Fiery Print Controller Standard Features	Fiery Hot Folders / Virtual Printers / Unity Display (Monitor required) / Fiery JDF / Fiery Command WorkStation5 / Paper Catalog /Fiery Spot-On / Fiery Remote Scan
Fiery Print Controller Options	Fiery Impose / Fiery Compose / Fiery Impose and Compose / Graphic Arts Package Premium Web Activate / Removable HDD Kit-B1 / Integration Interface and Stand (19" display, keyboard and mouse)
Dimensions (W x D x H)	215 mm x 483 mm x 485 mm

Paper Supply Options

Name	Cassette Feeding Unit-AM1
Paper Capacity	550 Sheets x 2 Cassettes (80 gsm)
Paper Size	A3, B4, A4, A4R, B5, B5R, A5R
Paper Weight	52 to 256 gsm
Power Source/Max. Power Consumption	From the Main Unit
**Dimensions (W x D x H)	620 mm x 700 mm x 251 mm (When attached with the Main Unit)
Weight	Approx. 22.5 kg
Name	High Capacity Cassette Feeding Unit-A1
Paper Capacity	2,450 sheets (80 gsm)
Paper Size	A4
Paper Weight	52 to 256 gsm
Power Source/Max. Power Consumption	From the Main Unit
**Dimensions (W x D x H)	620 mm x 700 mm x 251 mm (When attached with the Main Unit)
Weight	Approx. 30 kg
Name	Paper Deck Unit-F1
Paper Capacity	2,700 sheets (80 gsm)
Paper Size	A4, B5
Paper Weight	52 to 256 gsm
Power Source/Max. Power Consumption	From the Main Unit
Dimensions (W x D x H)	400 mm x 630 mm x 440 mm
Weight	Approx. 31 kg

Output Options

Name	Inner 2 Way Tray
Number of Trays*	2
Total Output Capacity	Upper Tray: 100 sheets Lower Tray: 250 sheets
Paper Weight	52 to 300 gsm
Paper Size	Standard size: A3, B4, A4, A4R, B5, B5R, A5, A5R, SRA3, Envelope (No.10(COM10), Monarch, DL, ISO-C5), Envelope Custom Size (98.0 mm x 98.4 mm to 320 mm to 457.2 mm) Custom Size: 98.0 mm x 139.7 mm to 320 mm x 457.2 mm
*Dimensions (W x D x H)	427 mm × 407 mm × 76 mm (When attached with the Main Unit)
Weight	Approx. 0.6 kg
Name	Inner Finisher-H1
Number of Trays	2
Top Tray Capacity	A4/B5/A5/A5R 45 sheets, A3/B4/A4R/B5R/SRA3 45 sheets
Lower Tray Capacity	A4/B5/A5/A5R 500 sheets, A3/B4/A4R/B5R/SRA3 250 sheets
Paper Weight	52 to 300 gsm
Staple Position	Corner, Double
Staple Capacity	Corner and Double Stapling: A4/B5: 50 sheets (52 to 90 gsm) A3/B4/A4R: 30 sheets (52 to 90 gsm) Eco Staple: A3/A4/B4/B5: 5 sheets (52 to 64 gsm) 4 sheets (65 to 81.4 gsm) 3 sheets (81.5 to 105 gsm) Staple On Demand: 40 sheets (80 gsm)
Dimensions (W x D x H)	466 mm × 525 mm × 225 mm
Weight	Approx. 8.6 kg
Name	Staple Finisher-Y1 (External)
Number of Trays	2
Upper Tray Capacity	A4/B5/A5/A5R 250 sheets, A3/B4/A4R/B5R/SRA3 125 sheets
Lower Tray Capacity	A4/B5/A5/A5R 3,000 sheets, A3/B4/A4R/B5R/SRA3 1,500 sheets
Paper Weight	Upper Tray: 52 to 256 gsm Lower Tray: 52 to 300 gsm
Staple Position	Corner, Double
Staple Capacity	Corner and Double Stapling: A4/B5: 50 sheets (52 to 90 gsm) A3/B4/A4R: 30 sheets (52 to 90 gsm) Eco Staple: A3/A4: 5 sheets (52 to 64 gsm) 4 sheets (65 to 81.4 gsm) 3 sheets (81.5 to 105 gsm) Staple On Demand: 50 sheets (90 gsm)
**Dimensions (W x D x H)	637 mm × 623 mm × 1,142 mm (When the extension tray is extended)
Weight	Approx. 31 kg
Name	Booklet Finisher-Y1
Number of Trays	2
Upper Tray Capacity	A4/B5/A5/A5R 250 sheets, A3/B4/A4R/B5R/SRA3 125 sheets
Lower Tray Capacity	A4/B5/A5/A5R 3,000 sheets, A3/B4A4R/B5R/SRA3 1,500 sheets
Paper Weight	Upper Tray: 52 to 256 gsm Lower Tray: 52 to 300 gsm
Staple Position	Corner, Double
Staple Capacity	Corner and Double Stapling: A4/B5: 50 sheets (52 to 90 gsm) A3/B4/A4R: 30 sheets (52 to 90 gsm) Eco Staple: A3/A4: 5 sheets (52 to 64 gsm) 4 sheets (65 to 81.4 gsm) 3 sheets (81.5 to 105 gsm) Staple On Demand: 50 sheets (90 gsm)
Booklet Stitch Paper Size	A3/B4/A4R, Custom Size (195 mm x 270 mm to 304.8 mm x 457.2 mm)
Booklet Stitch Staple Capacity	20 sheets x 10 sets (81 gsm) (Including 1 cover sheet up to 256 gsm)
**Dimensions (W x D x H)	637 mm × 623 mm × 1,142 mm (When the extension tray is extended)
Weight	Approx. 57 kg
Inner 2/3 Hole Puncher-B1	Two or Three Holes (Requires either the Inner Finisher-H1)
Acceptable Punch Paper Weight	52 to 300 gsm
Acceptable Punch Paper Size	Two holes: A3, B4, A4, A4R, B5, B5R Three holes: A3, B4, A4, B5
Power Source	From the Main Unit
Inner 2/4 Hole Puncher-B1	Two or Four Holes (Requires either the Inner Finisher-H1)
Acceptable Punch Paper Weight	52 to 300 gsm
Acceptable Punch Paper Size	Two holes: A3, B4, A4, A4R, B5, B5R Four holes: A3, A4
Power Source	From the Main Unit
2/3 Hole Puncher Unit-A1	Two or Three Holes (Requires either the Staple Finisher-Y1 or Booklet Finisher-Y1)
Acceptable Punch Paper Weight	52 to 300 gsm
Acceptable Punch Paper Size	Two holes: A3, B4, A4, A4R, B5, B5R Three holes: A3, B4, A4, B5
Power Source	From the Main Unit
2/4 Hole Puncher Unit-A1	Two or Four Holes (Requires either the Staple Finisher-Y1 or Booklet Finisher-Y1)
Acceptable Punch Paper Weight	52 to 300 gsm
Acceptable Punch Paper Size	Two holes: A3, B4, A4, A4R, B5, B5R Four holes: A3, A4
Power Source	From the Main Unit

Hardware Accessories

Tab Feeding Attachment-F1, Utility Tray-B1

Security Options

Document Security	Document Scan Lock Kit-B1, Secure Watermark-B1, Encrypted Printing Software-D1
Data Security	HDD Mirroring Kit-J1, 2.5 inch/250GB HDD-N1, 2.5 Inch/1TB HDD-P1, Removable HDD KIT-AL1

System and Controller Options

Print Accessories	PCL International Font Set-A1
Barcode Printing	Barcode Printing Kit-D1
EFI-Fiery Based Controller	imagePASS-P1, ColorPASS-GX500
EFI-Fiery Based Controller Options	Removable HDD KIT-B1, Fiery Impose, Fiery Compose, Fiery Impose and Compose
System Accessories	Web Access Software-K1, Serial Interface Kit-K3
FAX Accessories	Super G3 Fax Board-AS1, Super G3 2ND Line Fax Board-AS1, Super G3 3rd/4th Line Fax Board-AS1, Remote Fax Kit-A1

Other Options

Accessibility Accessories	ADF Access Handle-A1, Voice Guidance Kit-G1, Voice Operation Kit-D1
Consumables	Stamp Ink Cartridge-C1, Staple-P1, Staple Cartridge-Y1

Canon

canon.com.au/business
1800 444 199

No one does it like you