EXPECT *QUALITY* WITH SEAMLESS *PRODUCTIVITY*

Canon imageRUNNER ADVANCE

C7500i Series



The iR-ADV C7500i provides you with powerful productivity – putting you in the driver's seat and allowing you to produce and finish more jobs, faster. Expect consistent, quality output with advanced printing and finishing capabilities.

- Outstanding print quality with V2 colour and 2,400 dpi
- Finish with a range of production options
- Print paper weight up to 300 gsm
- Track, report and control usage
- Media handling thin, thick and textured stock

PERFORMANCE

Designed for a simple, tailored experience

- The large interface allows for easy navigation while My ADVANCE provides a personalised experience so you can customise your workflow in a way that works best for you
- Speed up processes with the single-pass document feeder and automatic blank page removal
- Achieve outstanding results with V2 imaging technology (V2 colour and true 2400dpi) and a range of finishing options including stapling, booklet, staple on-demand and eco staple

COST CONTROL

Advanced functions for big cost-saving

- Save your business money by reducing your paper wastage utilising settings such as forced job hold at the device, and blank page removal
- Enable print policies to monitor output while also restricting users from overuse
- Save even further with remote support to help diagnose and solve issues fast, rather than taking up the valuable time of in-house IT staff

INTEGRATION

Systems seamlessly converge for smooth operation and easy handling

- Canon's MEAP platform works to integrate both new and existing document, capture and output management systems while being partnered with relevant support technology
- Collaborate with key line of business applications and external systems
- For smooth, hassle-free projects, scan and convert to Microsoft® Word and PowerPoint® files

MOBILITY

Connect on-the-go

- Communicate remotely through WiFi, Bluetooth* and NFC*
- Give your team flexibility so projects don't need to stop just because they are away from the office
- Intuitive printing and scanning using Canon PRINT Business plus built in support for Apple® AirPrint®, Mopria™ and Google Cloud™

*Optional

Canon

No one does it like you

SECURITY

Protect sensitive information with enhanced security capabilities

- Advanced control over document access ensures documents are only seen by those that are authorised
- Functions used to monitor documents include user authentication, hard drive encryption, iPsec, port filtering capabilities and SSL technology
- The use of standard login management also means that tracking and reporting on various projects is feasible and can give insights into time and money spent on various projects

SUSTAINABILITY

Environmentally conscious technology works to achieve green initiatives for your business

- The iR-ADV C7500i runs efficiently to help eliminate unnecessary power consumption and is designed to reduce emissions
- Motion sensors, sleep recovery triggers, 100% recycled plastics, and remote shutdown are all features that contribute to ongoing sustainability
- Minimise paper wastage with default print settings including double-sided print and black and white
- ENERGY STAR® and Blue Angel qualified with class leading Typical Electricity Consumption (TEC) rating

CONFIGURATION

Staple Finisher

- 3-Tray, 4,250-sheet capacity (A4, B5, A5R)
- Corner and double stapling up to 100 sheets (A4/B5, 80 gsm), 50 sheets (A3/ B4/A4R, 80 gsm)
- Supports optional internal 2/3 and 2/4 hole inner punchers



Booklet Finisher

- 3-Tray, 4,250-sheet capacity (A4, B5, A5R)
- Corner and double stapling up to 100 sheets (A4/B5, 80 gsm), 50 sheets (A3/B4/A4R, 80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 5 sheets
- Supports optional internal 2/3 and 2/4 hole inner punchers






Upright Control Panel



Utility Tray



Copy Tray





Multi-Drawer Paper Deck

- Supports A3, B4, A4, A4R, B5R, B5, A5R, SRA3, 13" x 19"
- Media Weight 52-300 gsm
- 2,000 sheets x 3 drawers, total 6,000 sheets (80 gsm)

Document Insertion Unit

- Insert preprinted sheets
- Up to SRA3
- Two trays
- 400-sheet total capacity



Paper Folding Unit

- Z-fold, C-fold, Half Fold, Accordion Z-fold, Double Parallel Fold



Multi Function Professional Puncher

- Supports various die sets
- Up to 300 gsm
- Supports SRA3, A3, A4, A4R
- 70,000 chip tray capacity
- Enhanced die durability



colorPASS-GX500

- PS3/PCL6
- 4GB/1TB
- Fiery FS200 Pro



imagePASS-N1

- PS3/PCL6
- 2GB/500GB
- Fiery FS200



imageRUNNER ADVANCE C7500i Series

Main Unit

Type	Colour Laser Multifunction
Core Function	Print, Copy, Scan, Send, Store and Optional Fax
Processor	Canon Dual Custom Processor (Shared)
Control Panel	Standard: 25.6 cm (10.1 inch) TFT LCD WSVGA Colour Touchpanel Optional: 26.4 cm (10.4 inch) TFT LCD SVGA Colour Uprightpanel
Memory	Standard: 4GB RAM
Hard Disk Drive	Standard: 250GB Maximum: 1TB
Mirroring Hard Disk Drive	Optional: 250GB, 1TB
Interface Connection	Network: Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) Optional: NFC, Bluetooth Others: Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device) Optional: Serial Interface, Copy Control Interface
Paper Capacity (80gsm)	Standard: 3,500 Sheets Maximum: 9,300 Sheets
Paper Sources (80gsm)	Standard: Two 1,100-sheet Paper Deck, Two 550-sheet Paper Cassettes 250-sheet Multi-Purpose Tray Optional: 6,000-sheet Paper deck (Multi-Drawer Paper Deck-C1) Maximum: 9,300 Sheets (With Multi-Drawer Paper Deck-C1)
Paper Output Capacity (80gsm)	Standard: 250 Sheets Maximum: 3,450 Sheets
Finishing Capabilities	Standard: Collate, Group With External Finisher: Collate, Group, Offset, Staple, Booklet (Booklet Finisher-X1), Hole Punch (Puncher Unit-BF1 or Multi Function Professional Puncher-A1), Document Insertion (Insertion Unit-N1), Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold (Paper Folding Unit-J1), Trimming (Inner Trimmer-A1)
Supported Media Types	Upper Left/Right Cassettes(1/2): Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency, Bond paper, Letterhead Lower Cassettes (3/4): Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency, Tab paper, Bond paper, Envelope, Letterhead Multi-Purpose Tray: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Textured paper, Transparency, Tracing paper, Label, Tab paper. Bond paper, Coated paper, Envelope, Letterhead Multi-Drawer Paper Deck-C1: Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Textured paper, Transparency, Label, Tab paper, Bond paper, Coated paper, Letterhead
Supported Media Sizes	Upper Left/Right Deck (1/2): Standard Size: A4, B5 Lower Cassettes (3/4): Standard Size: A3, B4, A4, A4R, B5R, B5, A5R, SRA3, 13"x19" (330 mm x 483 mm), Envelope (No.10 (COM10), Monarch, ISO-C5, DL) Free Size: 139.7 mm x 182 mm to 330.2 mm x 487.7 mm, Custom Size: 139.7 mm x 182 mm to 330.2 mm x 487.7 mm, Envelope Custom Size: 98 mm x 148 mm to 330.2 mm x 487.7 mm Multi-Purpose Tray: Standard Size: A3, B4, A4, A4R, B5R, B5, A5R, SRA3, 13"x19" (330 mm x 483 mm), Custom Size: 100.0 mm x 148.0 mm to 330.2 mm x 487.7 mm, Free Size: 100 mm x 182 mm to 330.2 mm x 487.7 mm, Envelopes: No.10 (COM10), Monarch, ISO-C5, DL *Envelope specification, Size: Short-edge feed: No.10 (COM10), Monarch, ISO-C5, DL envelope, Custom Size: 90 mm x 148 mm to 330.2 mm x 487.7 mm Multi-Drawer Paper Deck-C1: Standard Size: A3, B4, A4, A4R, B5R, B5, A5R, SRA3, 13"x19" (330mm x 483 mm), Custom Size: 139.7 mm x 182 mm to 330.2 mm x 487.7 mm
Supported Media Weights	Upper Cassettes: 52 to 220 gsm Lower Cassettes: 52 to 256 gsm Multi-Purpose Tray: 52 to 300 gsm Duplex: 52 to 220 gsm
Warm-up Time	From Power On: 30 Seconds or Less (Time between device power-on and when the start key is enabled (print reservation)) From Deep Sleep Mode: 30 Seconds or Less Quick Startup Mode: 4 seconds or less
Dimensions (W x D x H)	689 mm x 941 mm x 1,220 mm
Installation Space (W x D)	Basic: 1,913 mm x 1,524 mm (when Stack Bypass open + Booklet Finisher-V2) Fully Configured: 3,818 mm x 1,524 mm (when Multi-Drawer Paper Deck-C1 + Document Insertion Unit-N1 + Multi Function Professional Puncher-A1 + Document Insertion Unit-N1 + Booklet Finisher-X1)
Weight*	Approx. 272kg *Including ADF and the toner bottle

Print Specifications

Printing Method	Colour laser beam printing
Print Speed (BW/Colour)	iR-ADV C7580i: 80/70 ppm (A4), 40/35 ppm (A3), 56.6/49.5 ppm (A4R), 80/70 ppm (A5R) iR-ADV C7570i: 70/65 ppm (A4), 35/32.5 ppm (A3), 49.5/46 ppm (A4R), 70/65 ppm (A5R) iR-ADV C7565i: 65/60 ppm (A4), 32.5/30 ppm (A3), 46/42.4 ppm (A4R), 65/60 ppm (A5R)
Print Resolution*	600 dpi x 600 dpi (Default), 1,200 dpi x 1,200 dpi (Up to) *Data processing resolution
Page Description Languages	UFR II, PCL6 (Standard) Adobe PS 3 (Option)
Double Sided Printing	Automatic (Standard)
Direct Print	Direct printing available from USB memory key, Advanced box, Remote UI and Web Access (Only PDF print from websites is supported) Supported File Types: PDF, TIFF, JPEG, EPS, XPS
Fonts	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T* (Japanese, Korean, Simplified and Traditional Chinese) , Barcode fonts** *Requires optional PCL International Font Set-A1 **Require optional Barcode Printing Kit-D1 PS fonts: 136 Roman
Operating System	UFRII: Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10, MAC OS X (10.6.8 or later) PCL: Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10 PS: Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10, MAC OS X (10.6.8 or later) PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows Vista/ Windows 7/Windows 8/Windows8.1/Windows10

Copy Specifications

Copy Speed (BW/Colour)	iR-ADV C7580i: 80/70 ppm (A4), 40/35 ppm (A3), 56.6/49.5 ppm (A4R), 80/70 ppm (A5R) iR-ADV C7570i: 70/65 ppm (A4), 35/32.5 ppm (A3), 49.5/46 ppm (A4R), 70/65 ppm (A5R) iR-ADV C7565i: 65/60 ppm (A4), 32.5/30 ppm (A3), 46/42.4 ppm (A4R), 65/60 ppm (A5R)
*First-Copy-Out Time (A4)	iR-ADV C7580i: Approx. 4.4 seconds or less (BW), Approx. 5.4 seconds or less (CL) iR-ADV C7570i: Approx. 4.8 seconds or less (BW), Approx. 5.9 seconds or less (CL) iR-ADV C7565i: Approx. 4.8 seconds or less (BW), Approx. 5.9 seconds or less (CL) *20 °C to 30 °C Environment
Copy Resolution	Reading: 600 dpi x 600 dpi Printing: 1,200 dpi x 1,200 dpi* *Data processing resolution
Multiple Copies	Up to 9,999 copies
Copy Exposure	Automatic or Manual (11 Levels)
Magnification	25% - 400% (1% Increments)
Preset Reductions	25%, 50%, 61%, 70%, 81%, 86%
Preset Enlargements	115%, 122%, 141%, 200%, 400%
Basic Copy Features	Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel
Special Copy Features	Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Copy ID Card, Detect Feeder Multi Sheet Feed. Free Size Original, Colour Balance, Adjust One-Touch Colour, Area Designation

Scan Specifications

Type	Colour Platen and Single-pass Duplexing Automatic Document Feeder
Document Feeder Paper Capacity	300 Sheets (80 gsm)
Document Feeder Supported Media Sizes	A3, B4, A4R, A4, B5R, B5, A5R, A5, B6R
Document Feeder Supported Media Weights	Single-sided scanning: 38 to 220 gsm (BW) Single-sided scanning: 64 to 220 gsm (CL) Double-sided scanning: 50 to 220 gsm (BW) Double-sided scanning: 64 to 220 gsm (CL)
Pull Scan Spec	Colour Network ScanGear2. For both Twain and WIA Supported OS: Windows Vista/7/8/8.1/10 Server 2008/Server 2008 R2/Server 2012/Server 2012 R2
Scan Resolution	100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi
Platen Acceptable Originals	Platen: Sheet, Book, 3-Dimensional Objects [Up to 2kg] Feeder Size: A3, B4, A4R, A4, B5R, B5, A5R, A5, B6R
Scan Speed (A4)	Single-sided Scanning (BW): 120 ipm (300pi) / 120 ipm (600 dpi) Single-sided Scanning (CL): 120 ipm (300pi) / 70 ipm (600 dpi) Double-sided Scanning (BW): 240 ipm (300pi) / 150 ipm (600 dpi) Double-sided Scanning (CL): 220 ipm (300pi) / 90 ipm (600 dpi)
Double Sided Scanning	2-sided to 2-sided (Automatic)

Send Specifications

Optional/Standard	Standard on all models
Destination	E-mail/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)
Colour Mode	Automatic-Colour Select (Full Colour/Grayscale), Automatic-Colour Select (Full Colour/Black-and-White), Full Colour, Grayscale, and Black and White
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Send Resolution	100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi
Communication Protocol	File: FTP, SMB , WebDAV E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)
File Format	Standard: TIFF, JPEG, PDF (Compact, Apply policy, Optimise for Web, PDF A/1-b), XPS (Compact) Optional: PDF (Searchable, Trace & Smooth, Encrypted), PDF/XPS (Digital Signature), Office Open XML (PowerPoint, Word), XPS (Searchable)

Fax Specifications

Optional/Standard	Optional on all models
Maximum Number of Connection Lines	4
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution	400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi
Sending/Recording Size	A5 and A5R* to A3 *Sent as A4
Fax Memory	Up to 30,000 pages
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 addresses
Memory Backup	Yes

Store Specifications

Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes, 30,000 Maximum Pages Stored
Advanced Box	Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows Vista/7/8/8.1/10) Concurrent Connections (Max.): SMB: 64, WebDAV: 3 (Active Sessions)
Advanced Box Available Disc Space	Approx. 16GB (Standard HDD) Approx. 480GB (1TB HDD)
Memory Media	Standard: USB Memory

Security Specifications

Authentication	Standard: Picture Login, DepartmentID Authentication, (Device and Function Level Log-in), Access Management System Optional: Universal Login Manager
Data	Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated) Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)
Network	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP
Document	Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration Optional: Encrypted PDF, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scan locking

Environmental Specifications

Operating Environment	Temperature: 10 to 30 °C (50 to 86 °F) Humidity: 20 to 80 % RH (no condensation)
Power Requirements	iR-ADV C7565i: 220-240 V (±10 %), 50/60 Hz (±2 Hz), 10 Amp iR-ADV C7570i: 220-240 V (±10 %), 50/60 Hz (±2 Hz), 10 Amp iR-ADV C7580i: 220-240 V (±10 %), 50/60 Hz (±2 Hz), 15 Amp
Power Consumption	Maximum:. iR-ADV C7580i 2.5 kW, iR-ADV C7570i/C7565i 2.0 kW Standby: Approx. 136.6 W (Reference Value) Sleep mode: Approx. 0.9 W (0.9W sleep mode is not available in all circumstances due to certain settings.) Typical Electricity Consumption (TEC) rating 5.6 kWh (iR-ADV C7580i), 4.8 kWh (iR-ADV C7570i), 4.5 kWh (iR-ADV C7565i)
Standards	ENERGY STAR® Qualified

Consumables

Toner	NPG-72 TONER BK/C/M/Y

Software and Printer Management

Remote Management Tools	iW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management) eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance) Content Delivery System: Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web-based interface to each device that helps to provide remote device management and control.
Scanning Software	Network ScanGear: TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device.
Optimisation Tools	Canon Driver Configuration Tool: A utility for changing the factory default settings of Canon print drivers (Available via service only) NetSpot Device Installer: Simple utility software that allows you to make network protocol settings for Canon devices connected to your network.
Platform	MEAP (Multifunctional Embedded Application Platform): A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device. MEAP Web: Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services
Document Publishing	iW Desktop: Powerful print publishing software which easily combines documents from different sources and file formats, applies finishing with preview and templates to create professional looking documents. Includes PDF creation, annotation and compression capabilities for simple digital workflows such as proofing and authorisation.

Fiery Print Controller Specifications

Optional/Standard	Optional on all models
Name	imagePASS-N1 (Embedded) and colorPASS-GX500
Print Resolution	1200 dpi x 1200 dpi, 600 dpi x 600 dpi
Standard Page Description Languages	Adobe PS3, PCL6
Memory	2 GB
Hard Disk Drive	500 GB
Processor	Intel Celeron G1820 2.7GHz
System	Fiery FS200
Fonts	PS: 138 Fonts PCL: 113 Fonts
Supported Operating Systems	Windows VISTA 32 and 64 bit / Windows 7 / 32 and 64 bit / Windows 8 32 and 64 bit / Windows 8.1 32 and 64 bit / Windows 10 32 and 64 bit / Windows Server 2008 32 and 64 bit / Windows Server 2008 R2 64 bit only / Windows Server 2012 64bit only / Windows Server 2012 R2 64bit only / MAC OS (10.7,10.8,10.9,10.10,10.11)
Interface	2 x Ethernet (1000Base-T/100Base- TX/10Base-T), USB3.0 x 2 (Rear x 2), USB2.0 x 4 (Rear x 4)
Network Protocols	TCP/IP (LPR/ Port 9100/ SNMP / IPP / HTTP/HTTPs / SMB / FTP) / DNS
Direct Print	PDF1.7, EPS, TIFF6, JDF1.4/JMF(OP)
VDP	FreeForm2.1
Fiery Print Controller Standard Features	Fiery Command WorkStation5 / Paper Catalog / Fiery Spot-On / Fiery Remote Scan / Hot Folders License
Fiery Print Controller Options	Fiery Impose / Fiery Compose / Fiery Impose and Compose / Productivity Package Web Activate (Include Fiery JDF)
Dimensions (W x D x H)	215 mm x 483 mm x 485 mm

Paper Supply Options

Name	Multi-Drawer Paper Deck-C1
Paper Capacity	6,000 sheets (80 gsm)
Paper Size	A3, B4, A4, A4R, B5R, B5, A5R, SRA3, 13" x 19"
Custom Size	139.7 mm x 182.0 mm to 330.2 mm to 487.7 mm
Paper Weight	52 to 300 gsm
Power Source	220-240V/1.7A 50/60Hz
Dimensions (W x D x H)	950 mm x 797 mm x 1,040 mm
Weight	Approx. 155 kg

Output Options

Name	**Copy Tray-R2**
Total Output Capacity	250 sheets (80 gsm)
Paper Weight	52 to 300 gsm
Paper Size	Standard Size: A3, B4, A4, A4R, B5R, B5, A5R, SRA3, 13"x19" (330 mm x 483 mm), Envelope (No.10 (COM10), Monarch, DL, ISO-C5), Custom Size: 100.0 mm x 148.0 mm to 330.2 mm x 487.7 mm Free Size: 100 mm x 182 mm to 330.2 mm x 487.7 mm Envelope Custom Size: 90 mm x 148 mm to 330.2 mm x 487.7 mm
Dimensions (W x D x H)	420 mm x 382 mm x 175 mm (When attached with the Main Unit/When the Extension Tray is extended)
Weight	Approx. 1.1 kg
Name	**Staple Finisher-X1** (External)
Number of Trays	3
Upper Tray Capacity	A4/B5/A5R: 1,500 sheets, A3/B4/A4R/B5R/SRA3/13" x 19": 750 sheets
Mid Tray Capacity	A4/B5/A5R: 250 sheets, A3/B4/A4R/B5R: 125 sheets
Lower Tray Capacity	A4/B5: 2,500 sheets (Cascade-Load mode)
Paper Weight	Top Tray: 52 to 300 gsm Mid Tray: 52 to 300 gsm Lower Tray: 52 to 300 gsm
Staple Position	Corner, Double
Staple Capacity	Corner staple and Double Staple: A4/B5: 100 sheets (52 to 80 gsm), A3/B4/A4R: 50 sheets (52 to 80 gsm)
Dimensions (W x D x H)	782 mm x 765 mm x 1,040 mm (When the Extension Tray is extended)
Weight	Approx. 64 kg

Name	**Booklet Finisher-X1** (External)
Number of Trays	3
Top Tray Capacity	A4/B5/A5R: 1,500 sheets, A3/B4/A4R/B5R/SRA3/13" x 19": 750 sheets
Mid Tray Capacity	A4/B5/A5R: 250 sheets, A3/B4/A4R/B5R: 125 sheets
Lower Tray Capacity	A4/B5: 2,500 sheets
Paper Weight	Top Tray: 52 to 300 gsm Mid Tray: 52 to 300 gsm Lower Tray: 52 to 300 gsm
Staple Position	Corner, Double
Staple Capacity	Corner staple and Double Staple: A4/B5: 100 sheets (52 to 80 gsm), A3/B4/A4R: 50 sheets (52 to 80 gsm)
Booklet Stitch Paper Size	A3/B4/A4R/SRA3S/13"x19", Custom Size: 210 mm x 279.4 mm to 330.2 mm x 487.7 mm
Booklet Stitch Staple Capacity	20 sheets x 5 sets (60 to 81.4 gsm) (Including 1 cover sheet up to 300 gsm)
Dimensions (W x D x H)	896 mm x 765 mm x 1,040 mm (When the Extension Tray is extended)
Weight	Approx. 110 kg
Name	**Inner Booklet Trimmer-A1** (Requires the Booklet Finisher-X1)
Waste Tray Capacity	1,500 Sheets
Acceptable Paper Weight	60 to 300 gsm
Power Source	From Finisher
Name	**Puncher Unit-BF1** (Requires either the Staple Finisher-X1 or Booklet Finisher-X1)
Acceptable Punch Paper Weight	52 to 256 gsm
Acceptable Punch Paper Size	Two holes A3/A4/A4R Three holes A3/A4
Power Source	From the Finisher
Name	**Puncher Unit-BG1** (Requires either the Staple Finisher-X1 or Booklet Finisher-X1)
Acceptable Punch Paper Weight	52 to 256 gsm
Acceptable Punch Paper Size	Two holes A3/A4/A4R/B5R Four holes A3/A4
Power Source	From the Finisher
Name	**Multi Function Professional Puncher-A1** (Requires either the Staple Finisher-X1 or Booklet Finisher-X1)
Acceptable Punch Paper Weight	Bypass: 52 to 300 gsm Punch: 75 to 300 gsm
Acceptable Punch Paper Size	A3/A4/A4R/SRA3
Supported Punch Dies (Optional)	Loose Leaf (2/4-hole, 4-hole) , Plastic Comb 21-hole, Velo Bind 12-hole, Twin Loop 23-hole/21-hole, Twin Loop 34-hole/32-hole, Twin Loop 23-hole, Twin Loop 34-hole, Colour Coil 47-hole
Dimensions (W x D x H)	445 mm x 795 mm x 1,040 mm
Weight	Approx. 102 kg
Name	**Document Insertion Unit-N1** (Requires either the Staple Finisher-X1 or Booklet Finisher-X1)
Number of Trays	2
Tray Capacity	Upper Tray: 200 Sheets (80 gsm) Lower Tray: 200 Sheets (80 gsm)
Acceptable Paper Weight	52 to 300 gsm
Acceptable Paper Type	Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Textured paper, Bond paper, Coated paper, Tab paper, Letterhead, Tracing paper
Acceptable Paper Sizes	A3/A4/A4R/B4/B5R/B5/SRA3/13" x 19", Custom Size: 182.0 mm x 182.0 mm to 3302. mm x 487.7 mm
Power Requirements	100-240V/50/60Hz 1.0A
Dimensions (W x D x H)	336 mm x 793 mm x 1,407 mm (Without Document Tray)
Dimensions (W x D x H)	746 mm x 793 mm x 1,407 mm (With Insertion Feeding Tray)
Weight	Approx. 61 kg
Name	**Paper Folding Unit-J1** (Requires either the Staple Finisher-X1 or Booklet Finisher-X1)
Folding Type	Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold
Acceptable Paper Weight	Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold: 52 to 105 gsm Double Parallel Fold: 52 to 90 gsm
Acceptable Paper Type	Thin paper, Plain paper, Colour paper, Recycled paper, Bond paper
Acceptable Paper Sizes	Z-Fold: A3/A4R/B4 Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold
Dimensions (W x D x H)	336 mm x 793 mm x 1,190 mm
Weight	Approx. 71 kg

Hardware Accessories

Card Readers	MiCard Plus Proximity Card Reader, IC Card Reader Box-B1
Others	Tab Feeding Attachment Kit-F1, Utility Tray-B1

Security Options

Document Security	Document Scan Lock Kit-B1, Secure Watermark-B1, Encrypted Secure Print Software-D1
Data Security	HDD Mirroring Kit-J1, 2.5inch/250GB HDD-N1, 2.5inch/1TB HDD-P1, Removable HDD Kit-AL1

System and Controller Options

Print Accessories	PCL International Font Set-A1, PCL Asian Font Set-A1
Barcode Printing	Barcode Printing Kit-D1
EFI-Fiery Based Controller	imagePASS-N1, colorPASS-GX500
EFI-Fiery Based Controller Options	Removable Hard Disk Drive Kit-B1, Fiery Impose, Fiery Compose, Fiery Impose and Compose
System Accessories	Web Access Software-K1, Serial Interface Kit-K3
Fax Accessories	Super G3 Fax Board-AS1, Super G3 2nd Line Fax Board-AS1, Super G3 3rd/4th Line Fax Board-AS1, Remote Fax Kit-A1

Other Options

Accessibility Accessories	ADF Access Handle-A1, Voice Guidance Kit-G1, Voice Operation Kit-D1
Consumables	Stamp Ink Cartridge-C1, Staple-N1, Staple-P1, Staple Cartridge-X1, Staple Cartridge-Y1

Canon

canon.com.au/business
1800 444 199

No one does it like you